

ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
1	MP Crossbar	Crossbar 14 Gauge Zinc Plated Steel 4.8" L x 4.8" W x .075" Material Thickness	1
2	#32	8/32 Green Ground Screw	1
3	MP Screws	6/32" x 3/4" Long Zinc Plated Flat Countersunk Head Machine Screw. Available with White, Black or Zinc Finished Heads	2
4	AC1-16-60G-HB	1/16" Cable w/60" HB Ends	2
5	MGR-SE-TH w/36CAB PD	Side Exit Gripper w/Through Hole for Crosscable for 1/16" Cable. Allen Set Screw on Bottom. 1.395" H x .354" W	2
6	#171	7/8" (.875") KO Strain Relief for 18/3,18/4,18/5 SJT Cord. Connector Snaps and Locks Around Cord Fits .290"385" Cord	2
7	6-SCCOIL 18/3	6' of 18/3 SJT Cord	1
8	#242B SQ SL RH WHT	Monopoint Canopy w/Cable Slots and 6/32" Mounting Hole & Raw Mounts875 Center Hole	1

			Pendant Systems 1670 Winchester Rd. Bensalem, PA 19020 P-215-638-8552 F-215-638-8554 www.PendantSystems.com		
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN BOTH INCHES & FINISH: MILLIMETERS UNLESS OTHERWISE NOTED TOLERANCES: + + + + + 1 Degree		Bill Of Materials			
DO NOT SCALE DRAWING	MATERIAL:	Part #			
DEBUR AND BREAK SHARP EDGES					REVISION
DRAWN DATE: 5/18/16	Drawn By: MWR	SCALE: NTS		SHEET 2 OF 2	