

PENDANT SYSTEMS

1670 Winchester Rd
PO Box 371
Bensalem PA 19020
PH- 215-638-8552
FAX- 215-638-8554

E-mail: Sales@PendantSystems.com
www.PendantSystems.com

Specification Sheet

PS Part# SC Coil 18/3 SVT CL Foil

Construction:

Conductors: 3-18 AWG (41/34) BC		Nom: 0.047" ± 0.002
Insulation: Premium Grade PVC	Wall: 0.0165"	Nom: 0.080" ± 0.004"
Color Code: Black-White-Green		
Cable: 3/C Cabled		Nom: 0.172" ± 0.010"
Shield: Aluminum Mylar Foil Shield Foil Out		Nom: 0.175" ± 0.010"
Jacket: Premium Grade UL PVC	Wall: 0.035"	Nom: 0.249" ± 0.010"
Color: Clear		

Note 1: Print/Markings on Product may vary to better suit Industry approvals

Note 2: Print Shall be indented

E-174416 18/2 SVT UL CSA 105°C 300V FT-2

Wire Processed Under Pendant Systems UL Wire Process # E325558



Approvals: RoHS UL 62 CSA-C22.2-49 Rating: 105°C 300V

"This Cable Design is the intellectual property of Pendant Systems Mfg. intended for use by Pendant Systems Mfg. and their customers. Treat this as a confidential controlled document"

Proprietary information

THIS DOCUMENT CAN ONLY BE DUPLICATED WITH THE WRITTEN PERMISSION FROM PENDANT SYSTEMS MFG.

Note All O.D.'s Are NOM