

PENDANT SYSTEMS

1670 Winchester Rd
PO Box 371
Bensalem PA 19020
PH- 215-638-8552
FAX- 215-638-8554

E-mail: Sales@PendantSystems.com
www.PendantSystems.com

Specification Sheet

PS Part# SC MB 18/5 LV

Construction:

Conductors: 5-18 AWG (16/30) BC		Nom: 0.049" ± 0.003"
Insulation: PVC 105°C, 80A Shore Durometer, 60-0600-43	Wall: 0.07"	Nom: 0.193" ± 0.005"
Color Code: Black-White-Green-Purple-Gray		
Cable: 5/C Cabled Around Flame Retardant Poly Filler	Lay: Left	
Shield: Braided Tinned Copper, 85% Coverage		Nom: 0.213" ± 0.005"
Jacket: Clear Pressured PVC	Wall: 0.034"	Nom: 0.335" ± 0.010"

Color: Clear

Note 1: Print/Markings on Product may vary to better suit Industry approvals

Note 2: Print Shall be indented

RU AWM E174416 105°C 300 V CSA AWM LL54185 I/II A/B 105°C 300V FT2

Wire Processed Under Pendant Systems UL Wire Process # E325558



Approvals: **RoHS** **UL 2661** **CSA** **AWM** **Rating: 105°C-300V**

"This Cable Design is the intellectual property of Pendant Systems Mfg. intended for use by Pendant Systems Mfg. and their customers. Treat this as a confidential controlled document"

Proprietary information

THIS DOCUMENT CAN ONLY BE DUPLICATED WITH THE WRITTEN PERMISSION FROM PENDANT SYSTEMS MFG.

Note All O.D.'s Are NOM