

PENDANT SYSTEMS

1670 Winchester Rd
PO Box 371
Bensalem PA 19020
PH- 215-638-8552
FAX- 215-638-8554

E-mail: Sales@PendantSystems.com
www.PendantSystems.com

Specification Sheet

PS Part# SC Coil 18/5 & 22/4

Construction:

Conductors: **5-18 41/34 BC to ASTM B-174**

Nom: **0.048"**

Insulation: **Premium Grade PVC**

Wall: **0.015"**

Nom: **0.078" ± 0.004"**

Color Code: **Black-White-Green-Black/White-White/Black**

Construction:

Conductors: **4-22 26/36 BC to ASTM B-174**

Nom: **0.030"**

Insulation: **Premium Grade PVC**

Wall: **0.015"**

Nom: **0.060" ± 0.004"**

Color Code: **Violet-Gray-Violet/White-Gray/White**

Cable: **Cable Conductors 1&2 to form
a 9 conductor composite cable**

Nom: **0.253" ± 0.010"**

Note 1: Length of Lay may be adjusted for roundness

Note 2: Overall layout of product rotation of conductors and or pair(s) may vary to insure best possible roundness and look of product

Jacket:

Wall: **0.035"**

Nom: **0.326" ± 0.010"**

Compound: **AMW**

Color: **See Note 4**

Note 3: Print/Markings on Product may vary to better suit Industry approvals. Print Shall be indented

*Note 4: This Specification Covers Jacket Color White-Black-Gray-*Clear *(has foil shield)*

E174416 RU AWM 2081 105°C 600V or 2661 105°C 300V VW-1 cRU AWM I/II A 105°C 600V FT-1



Approvals: **RoHS, REACH, California prop 165 UL 10958/2661/20811 CSA AWM Rating:
300V&600V/105°C**

"This Cable Design is the intellectual property of Pendant Systems Mfg. intended for use by Pendant Systems Mfg. and their customers. Treat this as a confidential controlled document"

Proprietary information

THIS DOCUMENT CAN ONLY BE DUPLICATED WITH THE WRITTEN PERMISSION FROM PENDANT SYSTEMS MFG

Note All O.D.'s Are NOM