

Pendant Systems

The Lighting Suspension Specialists www.PendantSystems.com P-215-638-8552 F-215-638-8554

Crosscables



| <u>Crosscables W/Threaded Captive Studs</u> | |
|---|--|
| <u>PS Part#</u> | <u>Description</u> |
| 8" Cross 1/4-20TH | 8"Long Crosscable W/Captive 1/4"-20 Studs |
| 12" Cross 1/4-20TH | 12"Long Crosscable W/Captive 1/4"-20 Studs |
| 18" Cross 1/4-20TH | 18"Long Crosscable W/Captive 1/4"-20 Studs |
| 24" Cross 1/4-20TH | 24"Long Crosscable W/Captive 1/4"-20 Studs |



| <u>Crosscables W/ Half Ball Ends</u> | |
|--------------------------------------|--|
| <u>PS Part#</u> | <u>Description</u> |
| AC1/16-7.25 HB x 2 | 7.25" Long Crosscable W/Half Ball Ends |
| AC1/16-8.5 HB x 2 | 8.5" Long Crosscable W/Half Ball Ends |
| AC1/16-10 HB x 2 | 10" Long Crosscable W/Half Ball Ends |
| AC1/16-12.5 HB x 2 | 12.5" Long Crosscable W/Half Ball Ends |
| AC1/16-18 HB x 2 | 18" Long Crosscable W/Half Ball Ends |
| AC1/16-24 HB x 2 | 24" Long Crosscable W/Half Ball Ends |
| AC1/16-36 HB x 2 | 36" Long Crosscable W/Half Ball Ends |



Slot Coupler

8/32" x 1/4"-20 Threaded Coupler for joining Slot Screw with TS 1/4-.25 on slotted extrusion (nickel plated)
0.83"H x 0.5"W




TS1/4-20-.5



TS1/4-20-.25

TS1/4-20-.5: Threaded Screw w/Slot 1/4"-20 Male x .5" Long Thread
TS1/4-20-.25: Threaded Screw W/Slot 1/4"-20 Male x .25" Long Thread



Slot Screw

8/32" Threaded Screw w/T-Slot Head (0.48"H) used to capture slotted extrusion (nickel plated)



#170 Acorn Nut

1/4"-20 Acorn Nut
Used on end of cable stud



Threaded Screws w/ Slots

Captures half ball end of cable with:

1. #104 Keps nut, or
2. #170 Acorn nut, or
3. Slot Coupler & Slot Screw to capture a slotted extrusion (i.e. LED Panel)



#104 Keps Nut

Used on end of cable stud



The above crosscable attachment methods can be used with the Cable Puck (page 30), Mono Point products (pages 13-23) as well as other crosscable assemblies.

