

PENDANT SYSTEMS

1670 Winchester Rd PO Box 371 Bensalem PA 19020 PH- 215-638-8552 FAX- 215-638-8554

E-mail: Sales@PendantSystems.com www.PendantSystems.com

Specification Sheet

PS Part# SC Coil 18/6 LV P

Construction:

Conductors: 6-18 AWG (16/30) BC

Insulation: **Premium Grade PVC**Nom: 0.032" ± 0.004"

Conductors Color Code: Purple-Pink-Red-Black-White-Green

Cable: 6/Conductors Cabled W/Binder Non-Woven Polyester Tape

Jacket: Polyvinyl Chloride (PVC) Oil, Moisture, UV Resistant, VW-1 Nom: 0.032" ± 0.05 "

Jacket Colors: White, Black (Suffix BK), GY(Suffix Gray), Clear (Suffix Clear)

Overall OD: Nom: $0.410" \pm 0.05"$

Note 1: Print/Markings on Product may vary to better suit Industry approvals

Note 2: Print Shall be indented. (Not Printed)

(UL) E322633 18/6 SJTOW 105C 300V FT-2

---c(UL) SJTOW 6/C 0.824mm2 (18 AWG) 105C 300V FT-2

(Also made under E46194)

Wire Processed Under Pendant Systems UL Wire Process # E325558

Environmental:

RoHS EU Directive 2011/65/EU (1&2&3), Reach 210,

California Prop 65: This product may contain chemicals known to the state of California to cause Cancer.

For more information go to www.P65Warnings.ca.gov

NEC Article 400 UL 62 CSA-C22.2-49 OSHA Rating: 105°C 300V

"This Cable Design is the intellectual property of Pendant Systems Mfg. intended for use by Pendant Systems Mfg. and their customers. Treat this as a confidential controlled document"

Proprietary information

THIS DOCUMENT CAN ONLY BE DUPLICATED WITH THE WRITTEN PERMISSION FROM PENDANT SYSTEMS MFG.