

PENDANT SYSTEMS

1670 Winchester Rd
PO Box 371
Bensalem PA 19020
PH- 215-638-8552
FAX- 215-638-8554

E-mail: Sales@PendantSystems.com
www.PendantSystems.com

Specification Sheet

PS Part# SC Coil 18/3 & 22/2-P

Construction:

Conductors: **3-18 41/34 BC**

Nom: **0.045"**

Insulation: **19920 PVC**

Wall: **0.016"**

Nom: **0.077" ± 0.004"**

Color Code: **Black-White-Green**

Construction:

Conductors: **2-22 26/36 BC**

Nom: **0.030"**

Insulation: **19920 PVC**

Wall: **0.015"**

Nom: **0.060" ± 0.004"**

Color Code: **Purple-Pink**

Cable: **22 AWG Purple-18 AWG Black-22 AWG Pink** Lay: **3.00 LHL**
18 AWG White-18 AWG Green with O/A NWT

Nom: **0.194" ± 0.010"**

Note 1: Length of Lay may be adjusted for roundness

Note 2: Overall layout of product rotation of conductors and or pair(s) may vary to insure best possible roundness and look of product

Jacket:

Wall: **0.038"**

Nom: **0.260" ± 0.010"**

Compound: **157-V**

Color: **See Note 4**

Note 3: Print/Markings on Product may vary to better suit Industry approvals. Print Shall be indented

Note 4: This Specification Covers Jacket Colors White-Black-Gray

E174416 RU AWM 20811 105°C 600V or 2661 105°C 300V VW-1 cRU AWM I/II A 105°C 600V FT-1

Wire Processed Under Pendant Systems UL Wire Process # E325558



Approvals: **RoHS 1, 2 & 3**

UL 10958/2661/20811

CSA

AWM Rating: 300V&600V/105°C

"This Cable Design is the intellectual property of Pendant Systems Mfg. intended for use by Pendant Systems Mfg. and their customers. Treat this as a confidential controlled document"

Proprietary information

THIS DOCUMENT CAN ONLY BE DUPLICATED WITH THE WRITTEN PERMISSION FROM PENDANT SYSTEMS MFG.

Note All O.D. 's Are NOM