

PENDANT SYSTEMS

1670 Winchester Rd
PO Box 371
Bensalem PA 19020
PH- 215-638-8552
FAX- 215-638-8554

E-mail: Sales@PendantSystems.com
www.PendantSystems.com

Specification Sheet

PS Part# SC Coil 18/4 CL Foil

Construction:

| | | |
|--|---------------------|-----------------------------|
| Conductors: 4-18 AWG (41/34) BC | | Nom: 0.047" |
| Insulation: Premium Grade PVC | Wall: 0.015" | Nom: 0.077" ± 0.004" |
| Color Code: Black-White-Red-Green | | |
| Cable: 4/C Cabled Around Solid Filler | Lay: Left | Nom: 0.186" ± 0.010" |
| Shield: Aluminum Mylar Foil Shield Foil Out | | Nom: 0.189" ± 0.010" |
| Jacket: Premium Grade UL PVC | Wall: 0.035" | Nom: 0.259" ± 0.010" |
| Color: Clear | | |

Note 1: Print/Markings on Product may vary to better suit Industry approvals

Note 2: Print Shall be indented

E174416 RU AWM 2661 105°C 300V VW-1 cRU AWM I/II A/B 105°C 600V FT-1

Wire Processed Under Pendant Systems UL Wire Process # E325558



Approvals: **RoHS** **UL 2661** **CSA** **AWM** **Rating: 105°C – 300V&600V**

"This Cable Design is the intellectual property of Pendant Systems Mfg. intended for use by Pendant Systems Mfg. and their customers. Treat this as a confidential controlled document"

Proprietary information

THIS DOCUMENT CAN ONLY BE DUPLICATED WITH THE WRITTEN PERMISSION FROM PENDANT SYSTEMS MFG.

Note All O.D. 's Are NOM