

ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
1	MP Crossbar	Crossbar 14 Gauge Zinc Plated Steel 4.8" L x 4.8" W x .075" Material Thickness	1
2	#32	8/32 Green Ground Screw	1
3	MP Screws	6/32" x 3/4" Long Zinc Plated Flat Countersunk Head Machine Screw. Available with White, Black or Zinc Finished Heads	2
4	AC1-16-[XX]G HB	1/16" Cable w/60" HB End1/16" Galvanized Cable Fuse Cut with Die Cast #2 Half Ball Stop Available in 24", 36", 60", 120", 180", & 240" Lengths 7x7 Cable	2
5	MGR-SE-TH w/36CAB PD	Side Exit Gripper w/Through Hole for Crosscable for 1/16" Cable. Allen Set Screw on Bottom. 1.395" H x .354" W	2
6	171	.875" KO Strain Relief for 18/3, 18/4 & 18/5 SJT Cord Connector Snaps and Locks around Cord Fits .290"385" Cord	2
7	SCCOIL 18/3	18/3 SJT Cord	1
8	#242B SQ SL RH WHT	Monopoint Canopy w/Cable Slots and 6/32" Mounting Hole & Raw Mounts875 Center Hole	1

			This Document Contains Proprietory Data that is property of Pendant Systems which reserves all rights to it. Unauthorized use without authorization is prohibited.		dant Systems 1670 Winchester Rd. Bensalem, PA 19020 P-215-638-8552 F-215-638-8554 w.PendantSystems.com	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN BOTH INCHES & MILLIMETERS UNLESS OTHERWISE NOTED TOLERANCES: LINEAR: XX= .02" XXX= -010" ANGULAR: + 1 Degree		FINISH:	Bill Of Materials			
DO NOT SCALE DRAWING		MATERIAL: Part #				
DEBUR AND BREAK SHARP EDGES						REVISION
DRAWN DATE: 5/18/16		Drawn By: MWR	SCALE: NTS		SHEET 2 OF 2	