	QTY.					
3 #34ADJ 3/8" IP Slip Half Ball Bright Casting 3 #34ADJ 3/8" IP Slip Half Ball Bright Casting 4 MP Plate Monopoint Plate for Half Ball for MP Crossbar 2.82" Lx 1.650" W x.075" Material Thickness 7 4 MP Plate Monopoint Plate for Half Ball for MP Crossbar 2.82" Lx 1.650" W x.075" Material Thickness 8 6 #237 Mono Point Swivel Retaining Clip for MP-Plate HB Spring Steel 6 #237 875" Hole Bushing .945" W x.750" LD. x.250" H .063" Max Panel Thickness 7 Magnet #6 & #8 Magnet 8 271 6/32" x 1/4" L Flat Head Philips Machine Screw 9 183 8/32" x 1/4" Philip Head Ext Sems Steel Zinc Screw 9 183 8/32" x 1/4" L Pint Head Philips Machine Screw 9 183 8/32" x 1/4" Philip Head Ext Sems Steel Zinc Screw 10 #ADJ-SS 1/4" -20 Socket Set Screw w/.125" DIA Point & 1/8" Allen Hex Head Pin for ADJ Series Half Balls 11 #SSS 1/4" Philipple 1" L 13 #25 1/4" IP Nilpple 1" L	1					
2 3 #34ADJ 3/8" IP Slip Half Ball Bright Casting 2 4 MP Plate Monopoint Plate for Half Ball for MP Crossbar 2.82" L x 1.650" W x JOT" 2.82" L x 1.650" W x JOT" 2.82" L x 1.650" W x JOT" 2.82" L x 1.650" W x JOT" 4 MP Plate Material Thickness Half Ball Opening for #35,#34 and #147 7 Tapped 8/32" Hole Zinc Plated Steel 5 MP Swivel Clip Mono Point Swivel Retaining Clip for MP-Plate HB Spring Steel 6 #237 .875" Hole Bushing .945" W x.750" I.D. x .250" H .063" Max Panel Thickness 7 Magnet #6 & #8 Magnet 8 271 6/32" x 1/4" Philip Head Ext Sems Steel Zinc Screw 9 183 8/32" x 1/4" Philip Head Ext Sems Steel Zinc Screw 10 #ADJ-SS DIA Point & 1/8" Allen Hex Head Pin for ADJ Series Half Balls 11 #SSS 1/4" -20 Shoct (.350" Long) Socket Set Screw W/.125 DIA Point & 1/8" Allen Hex Head Pin for ADJ Series Half Balls 12 49-1 1/4" IP Nipple 1" L 13 #25 1/4" IP Nipple 1" L	1					
Image: Construction of the second	1					
8 7 4 6 7 8 6 #237 8 875" Hole Bushing .945" W 7 Magnet 8 271 6 4 9 183 8 271 6 3 7 Magnet 8 271 6 4 9 183 8 271 6 3 9 183 8 271 9 183 8 271 10 #ADJ-SS 10 #ADJ-SS 10 #ADJ-SS 11 #SSS 11 #SSS 12 49-1 13 #25 1/4" IP Nipple 1"L 13 #25	1					
4 6 #237 .875" Hole Bushing .945" W X750" I.D. x. 250" H.063" Max Panel Thickness 7 Magnet #6 & #8 Magnet 8 271 6/32" x 1/4" L Flat Head Philips Machine Screw 9 183 8/32" x 1/4" Philip Head Ext Sems Steel Zinc Screw 9 183 8/32" x 1/4" Philip Head Ext Sems Steel Zinc Screw 10 #ADJ-SS I/4" -20 Short (.350" Long) Socket Set Screw w/.125" 10 #ADJ-SS DIA Point & 1/8" Allen Hex Head Pin for ADJ Series Half Balls 11 #SSS 1/4" -20 Socket Set Screw w/.125" 11 #SSS 1/4" -20 Socket Set Screw w/.125" 13 #25 1/4" IP Nipple 1" L 13 #25 1/4" IP Nipple 1" L	1					
1 10	1					
8 2/1 Philips Machine Screw 9 183 8/32" x 1/4" Philip Head Ext Sems Steel Zinc Screw 9 183 8/32" x 1/4" Philip Head Ext Sems Steel Zinc Screw 10 #ADJ-SS 1/4" -20 Short (.350" Long) Socket Set Screw w/.125" DIA Point & 1/8" Allen Hex Head Pin for ADJ Series Half Balls 11 #SSS 1/4" -20 Socket Set Screw w/.125 DIA & 1/8" Allen Hex Head Pin for ADJ Series Half Balls 11 #SSS 1/4" -20 Socket Set Screw w/.125 DIA & 1/8" Allen Hex Head Pin for ADJ Series Half Balls 12 49-1 1/4" IP Nipple 1" L 13 #25 1/4" IP x 11/16 O.D. x 1/8" Thick Zinc Plated	2					
910#ADJ-SS1/4" -20 Short (.350" Long) Socket Set Screw w/.125" DIA Point & 1/8" Allen Hex Head Pin for ADJ Series Half Balls1211#SSS1/4" -20 Socket Set Screw w/.125 DIA & 1/8" Allen Hex Head Pin for ADJ Series Half Balls131249-11/4" IP Nipple 1" L13#251/4" IP x 11/16 O.D. x 1/8" Thick Zinc Plated	2					
1 9 10 #ADJ-SS Socket Set Screw w/.125" DIA Point & 1/8" Allen Hex Head Pin for ADJ Series Half Balls 12 11 #SSS 1/4" -20 Socket Set Screw w/.125 DIA &1/8" Allen Hex Head Pin for ADJ Series Half Balls 13 12 49-1 1/4" IP Nipple 1" L 13 #25 1/4" IP x 11/16 O.D. x 1/8" Thick Zinc Plated	1					
12 11 #SSS w/.125 DIA &1/8" Allen Hex Head Pin for ADJ Series Half Balls 13 12 49-1 1/4" IP Nipple 1" L 13 #25 1/4" IP x 11/16 O.D. x 1/8" Thick Zinc Plated	1					
13 #25 1/4" IP x 11/16 O.D. x 1/8" Thick Zinc Plated	1					
13 #25 Thick Zinc Plated	1					
14 #32 8/32 Green Ground Screw	1					
	1					
STEM LENGTH WILL VARY. ORDER SEPARATELY MP SW3/8 RD MAG ADJ ID USED WITH STEM 3/8" IP I.D. PH 3/8" IPS .625"635" O.D. 18 T.P.I Add Suffix WHT for White or BK for Black *45° SWIVEL						
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN BOTH INCHES & FINISH: MILLIMETERS UNLESS OTHERWISE NOTED TOLERANCES: LINEAR: XX = .02" XXX =						
DO NOT SCALE DRAWING MATERIAL: Part # DEBUR AND BREAK SHARP EDGES REV	evision					
DRAWN DATE: 4/4/17 Drawn By: MWR SCALE: NTS SHEET 1 OF 2						

		without authorization	1670 Winchester Ro Bensalem, PA 1902 P-215-638-8552 F-215-638-8554 ww.PendantSystems	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN BOTH INCHES & MILLIMETERS UNLESS OTHERWISE NOTED TOLERANCES: LINEAR: XX = .02" XXX =	FINISH:	MP SW 3-8 RD MAG	G ADJ ID Assemb	led
DO NOT SCALE DRAWING DEBUR AND BREAK SHARP EDGES	MATERIAL:	Part #		REVISION
DRAWN DATE: 4/4/17	Drawn By: MWR	SCALE: NTS	SHEET 2 OF 2	