Pendant Systems

Specification Sheet

PS Part# SC Coil 22/4 AWM

Construction:		
Conductors: 4-22 AWG (26/36) BC to ASTM B-174		Nom: 0.033 "
Insulation: Premium Grade PVC	Wall: 0.015"	Nom: 0.063" ± 0.004"
Color Code: Blue/Blue-White/Red/Red-Wh	ite	
Cable: 4/C Cabled		Nom: 0.152 "
Jacket: Premium Grade UL PVC	Wall: 0.035"	Nom: 0.225" ± 0.010"
Color: White-Black-Gray-Clear		
Note 1: Print/Markings on Product may vary	to better suit Industry approvals	
Note 2: Print Shall be indented		

E174416 RU AWM 20811 105°C 600V or 2661 105°C 300V VW-1 cUR AWM I/II A 105°C 600V FT1

Wire Processed Under Pendant Systems UL Wire Process # E325558



Approvals: RoHS

UL AWM 2661

CSA

Rating: 105°C - 300V/600V

"This Cable Design is the intellectual property of Pendant Systems Mfg. intended for use by Pendant Systems Mfg. and their customers. Treat this as a confidential controlled document"

Proprietary information

THIS DOCUMENT CAN ONLY BE DUPLICATED WITH THE WRITTEN PERMISSION FROM PENDANT SYSTEMS MFG.

Note All O.D.'s Are NOM