

PENDANT SYSTEMS

1670 Winchester Rd
PO Box 371
Bensalem PA 19020
PH- 215-638-8552
FAX- 215-638-8554

E-mail: Sales@PendantSystems.com
www.PendantSystems.com

Specification Sheet

PS Part# SC MB 18/3 600V

Construction:

| | | |
|--|---------------------|-----------------------------|
| Conductors: 3-18 (16/30) BC | | Nom: 0.049" |
| Insulation: PVC | Wall: 0.020" | Nom: 0.092" ± 0.002" |
| Color Code: Black-White-Green | | |
| Cable: 3/C Cabled Poly Filler | Lay: Left | Nom: 0.204" ± 0.005" |
| Shield: Braided Tinned Copper, 85% Coverage | | Nom: 0.226" ± 0.005" |
| Jacket: Pressured PVC | Wall: 0.030" | Nom: 0.285" ± 0.005" |
| Color: Clear | | |

Note 1: Print/Markings on Product may vary to better suit Industry approvals

Note 2: Print Shall be indented

RU AWM E54661 105°C 600V CSA AWM LL54185 I/II A/B 105°C 600V FT-2

Wire Processed Under Pendant Systems UL Wire Process # E325558



Approvals: **RoHS** **AWM 2586** **105°C 600V**

"This Cable Design is the intellectual property of Pendant Systems Mfg. intended for use by Pendant Systems Mfg. and their customers. Treat this as a confidential controlled document"

Proprietary information

THIS DOCUMENT CAN ONLY BE DUPLICATED WITH THE WRITTEN PERMISSION FROM PENDANT SYSTEMS MFG.

Note All O.D. 's Are NOM