## PENDANT SYSTEMS

1670 Winchester Rd PO Box 371 Bensalem PA 19020 PH- 215-638-8552 FAX- 215-638-8554

E-mail: <u>Sales@PendantSystems.com</u> www.PendantSystems.com

## **Specification Sheet**

## PS Part# SC Coil 18/5 CL LV

Construction:

Conductors: 5-18 41/34 BC Nom: 0.045"

Insulation: 19920 PVC Wall: 0.016" Nom: 0.077" ± 0.004"

Color Code: Black-White-Green-Purple-Gray

Cable: 5/C Cabled Around Solid Filler with O/A AMA Lay: 3.00 LHL Nom: 0.212" ± 0.010"

Note 1: Conductor Rotation to be As shown As Cable Pays Off Reel

Jacket: Clear Wall: 0.038" Nom: 0.288" ± 0.010"

Color: Clear

Note 2: Print/Markings on Product may vary to better suit Industry approvals

Note 3: Print Shall be indented

## E174416 RU AWM 2661 105°C 300V VW-1 cRU I/II A 105°C 600V FT-1

Wire Processed Under Pendant Systems UL Wire Process # E325558



Approvals: RoHS UL 1569/2661 CSA AWM Rating: 105°C -300V&600V

"This Cable Design is the intellectual property of Pendant Systems Mfg. intended for use by Pendant Systems Mfg. and their customers. Treat this as a confidential controlled document"

Proprietary information

THIS DOCUMENT CAN ONLY BE DUPLICATED WITH THE WRITTEN PERMISSION FROM PENDANT SYSTEMS MFG.

Note All O.D. 's Are NOM