

PENDANT SYSTEMS

1670 Winchester Rd
PO Box 371
Bensalem PA 19020
PH- 215-638-8552
FAX- 215-638-8554

E-mail: Sales@PendantSystems.com
www.PendantSystems.com

Specification Sheet

PS Part# SC MB 18/3 THK

Construction:

Conductors: **3-18 AWG (41/34) BC**

Insulation: **Semi-Rigid PVC**

Wall: **0.015"** Nom: **0.079" ± 0.002"**

Color Code: **Black-White-Green**

Cable: **3/C Cabled with a Paper Filler**

Lay: **Left** Nom: **0.185" ± 0.005"**

Shield: **Braided Tinned Copper, 85% Coverage**

Nom: **0.210" ± 0.005"**

Jacket: **Clear Pressured UL CSA PVC 105°C-300V**

Wall: **0.030"** Nom: **0.275" ± 0.005"**

Color: **Clear**

Note 1: Print/Markings on Product may vary to better suit Industry approvals

Note 2: Print Shall be indented

E54661 RU AWM 105°C – 300V CSA AWM 21048 LL54185 I/II A/B 105°C – 600V FT-1

Wire Processed Under Pendant Systems UL Wire Process # E325558



Approvals: **RoHS**

UL 2661

CSA

AWM 21048

Rating: 105°C – 300V&600V

"This Cable Design is the intellectual property of Pendant Systems Mfg. intended for use by Pendant Systems Mfg. and their customers. Treat this as a confidential controlled document"

Proprietary information

THIS DOCUMENT CAN ONLY BE DUPLICATED WITH THE WRITTEN PERMISSION FROM PENDANT SYSTEMS MFG.

Note All O.D. 's Are NOM