

Pendant Systems

The Lighting Suspension Specialists www.PendantSystems.com P-215-638-8552 F-215-638-8554

Cable Accessories



TS 1/4-20 TH

1/4"-20 Bolt with hole for cable often used on crosscables to fasten cable end into Fixture
.616"L x .452"W x .5"Thread



TS 1/4-20

1/4"-20 Cable Coupler
Used into bottom of side exit 1/4"-20 Gripper (MGR-SE 1/4-20) to capture crosscable
.366"H x .450"W x .2"Thread



CC1/16

Cross Cable Coupler W/ Allen Screw Accepts Stop End of Cable and Marries Cable End to Crosscable
.669"L x .273"W



CC1/8 SO

Standoff W/1/8"IP Cap for Cable Stops Base has .2" Hole in Base for Screw and Hole for Cable Side Exit when used w/ MGR1/8"IP
1.23"H x .5"W



Snap Hook

Hook 2"L x 1.25"W x .55" Bail Opening, Nickel Plated Brass. Can be used with Cable Coupler or MGR-SE1/4"-20 Gripper.



CCH-SVT

Cable & Cord Holder
1.232"L x .351"W
.275"Cord Hole Diameter Works well with SVT Cord like our Metal Braid Cord



CCH-SJT

Cable & Cord Holder
1.232"L x .482"W
.380"Cord Hole Diameter Works well with 18/3, 18/4 & 18/5 SJT Cord



Cable Collar

W/Allen Set Screw
.280"W x .184"H x .125"ID
No-5-40 set screw .125" long
1/16" Hex inserted into part



112 (3/32 Cable) 112-1/16" (1/16" Cable) 112-3/64" (3/64" Cable)

Cable Loop Adapter
Duplex Ferrule Can be crimped
Used to make Loops with Stop End of Cables



WRC 5/64 SS

5/64" Wire Rope Clip



A3/8IP x 1/4-20

3/8"IP x 1/4"-20 Adapter
1.1" L x .782" OD x .5"
1/4"-20 thread length



WRC 1/16

Wire Rope Clip for 3/64", 1/16" & 3/32" Cable




13052- FL

Curved Balancer for capturing 1/16" crosscables
Used with MGR 10/32" Gripper



PD 1/16

1/16" Paddle Galvanized Steel. Paddle used with the stop end of cable. When pushed through 1/4"hole it will not allow cable to exit hole.



CCC-1

Cross Cable Coupler for joining two cables together
.560"H x .633" across flats



A3/8IP x 1/4-20 F

Adapter 3/8 IP male x 1/4 in.-20 female
.885" W x .426" H x .325"
-3/8 IP thread

Pendant Systems

The Lighting Suspension Specialists www.PendantSystems.com P-215-638-8552 F-215-638-8554

Cable Grippers & Accessories



CC1/4-202P

2-Piece Cable Coupler
Threaded 1/4"-20 Female
1"H x .491"W x 1/2" of
1/8"IP Thread on OD for
Coupler to Retain Canopy



CC1/4-202P NK

2-Piece (No Knurling) Cable
Coupler Threaded 1/4"-20 Fe-
male
1"H x .491"W x 1/2" of 1/8"IP
Thread on OD for
Coupler to Retain Canopy



CC1/4-20

1-Piece Cable Coupler
Threaded 1/4"-20 Female
1"H x .459"W
Accepts Stop End of Cable



CC1/4-20-M

1-Piece Cable Coupler
Threaded 1/4"-20 Female
1"H x .359"W
Accepts Stop End of Cable
Available White & Black



CC1/4-20-M-FL

1-Piece Cable Coupler
Threaded 1/4"-20 Female
1.25"H x .359"W. Accepts
Stop End of 1/16" Cable
CC1/4-20-M-FL 3/32
Accepts Stop End of 3/32"



CC-Slot

2-Piece Cable Coupler
Bottom Piece Threaded
1/4"-20 Female
.817"H x .588"W
Used on Angled Ceilings



CC-Slot 1/4IP

Cable Coupler
Threaded 1/4"IP Female
.750"H x .589"L x 1/4"IP
Used on Angled Ceilings



CC3/8-3 & CC3/8-4

Multiple Cable Couplers
3 & 4 Hole Styles Available
1.189"L x .784"W x 3/8"IP
Holds Stop End of Cable



113

Cable Locking Tube
.793"L x .235"W
2-Screws inserted at each end



BC

1/8"IP Barrel Coupler
.509"L x .491"W x 1/8"IP



CC1/8 Cap

1/8"IP Male Threaded Cap
with Thru hole for 3/64" &
1/16" Cable Used with
CC1/8 SO



CC-Screw 1/4-20

1/4"-20 Screw with Thru Hole
Used with 3/64", 1/16", & 3/32"
Cable. Captures Stop Ends &
Half Balls of Cables



CC1/8 SO Rev-1

Standoff W/1/8"IP Cap for Cable
Stops Base has .2" Hole in Base
for Screw and Hole for Cable
Side Exit when used w/
MGR1/8"IP
1.23"H x .5"W
1/4"-20 Female Thread in Base



CG CR Wide

Adapter for CG Cap or CG CC
for mounting into #45 Canopy.
.765" W x .309" L



CG CC

1/8" IP Cable Coupler for air craft
cable stop, used with CG CR
Wide
.765" W x .309" L



CC-Screw

5/16"-18 x 7/8"L Side Mount
Aluminum Cable Coupler .875"
Thread (.312"OD), Head .469"
x .313" W/Flats Accepts Cable
Stop at 90 Degrees



CC-SO

Cable Coupler 2-Piece Cable
Coupler 1.03"H x .470"W



CC-Swivel Eyelet

Coupler 1.102"H @90
x .492"W x .422" 1/4"-20
Thread x .256" Hole



CC-Mini SO

Cable Coupler 2-Piece Cable
Coupler .472"H x .456"W
HB Ball End Cable Needed