

T-Bar Clip  
Fits 15/16" & 9/16 T-Bar  
Bolt Slot Grid Clip Available

2" Canopy Wht or Blk  
Can be Round or Square

CC1/4-20-M  
Cable Coupler

Main Cable Length

Eye Opening  
.172" Max

.087" (2.2 MM)  
Snap Hook Post

Adjustable Set Screw  
for Fixture Balance

24.5"

| Part# Variations FP-XXX TB SW-EYE |
|-----------------------------------|
| XXX (Main Cable)                  |
| 60" Cable                         |
| 120" Cable                        |
| 180" Cable                        |
| 240" Cable                        |

Flat Panel T-Bar Kit with Swivel Eye  
Snap Hooks & 3/64" 7 x 7 Galvanized Cable  
Applications: T-Bar Mount 2-Pack(Suffix-S Single Pack) Max Safe Static Load- 10 Lbs / Cable 10 Lb Fixture 5 X Safety Factor

This Document Contains Proprietary Data that is property of Pendant Systems which reserves all rights to it. Unauthorized use without authorization is prohibited.

**Pendant Systems**  
1670 Winchester Rd.  
Bensalem, PA 19020  
P-215-638-8552  
F-215-638-8554  
www.PendantSystems.com

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN BOTH INCHES & MILLIMETERS UNLESS OTHERWISE NOTED TOLERANCES:  
LINEAR: XX= .02" XXX=  $\pm .010$ " ANGULAR:  $\pm 1$  Degree

FINISH:  
Zinc / Nickel

Part #  
FP-XXX TB SW-EYE

DO NOT SCALE DRAWING  
DEBUR AND BREAK SHARP EDGES

MATERIAL: Brass / Steel

Title:  
REVISION

DRAWN DATE: 3/28/23

Drawn By: MCL

SCALE: NTS

SHEET 1 OF 1