

Flat Panel Universal Suspension Kit with Swivel Eye Snap Hooks & 3/64" 7 x 7 Galvanized Cable Applications: Drywall, Steel Deck & Loop Around Structure using Duplex Ferrule 2-Pack (Suffix-S Single Pack)Max Safe Static Load- 10 Lbs / Cable

This Document
Contains Proprietory
Data that is property
of Pendant Systems
which reserves all
rights to it.
Unauthorized use
without authorization
is prohibited.

Part #

1670 Winchester Rd. Bensalem, PA 19020 P-215-638-8552 F-215-638-8554 www.PendantSystems.com

<u> 1016 Fixture 5 X Satety Factor</u>
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN BOTH INCHES &
MILLIMETERS UNLESS OTHERWISE NOTED TOLERANCES:
+ +
LINEAR: XX= .02" XXX=010" ANGULAR: - 1 Degree

3/24/23

DRAWN DATE:

FINISH:	
Zinc /	Nickel

Drawn By: MCL

FP-XXX UNIV SW-EYE

DO NOT SCALE DRAWING	MATERIAL:	Brass / Steel	Title:
DEBUR AND BREAK SHARP EDGES			

SCALE: NTS

SHEET 1 OF 1

REVISION