1670 Winchester Rd
PO Box 371
Bensalem PA 19020
PH- 215-638-8552
FAX- 215-638-8554
E-mail: Sales@PendantSystems.com
www.PendantSystems.com

PENDANT SYSTEMS

Specification Sheet

PS Part# LSC Coil 18/3

Construction:

Conductors: **3-18 41/34 BC** Nom: **0.045”**

Insulation: **19920 PVC** Wall: **0.016”** Nom: **0.077” ± 0.004”**

Color Code: **Black-White-Green**

Cable: Lay: **3.00 LHL** Nom: **0.194” ± 0.010”**
18 AWG Black-18 AWG White-18 AWG Green with O/A NWT

Steel Cable: 1/16” 7 x 7 Strand Steel Galvanized Cable .0625” Diameter W/ PVC Insulation .093” Diameter
Note 1: Length of Lay may be adjusted for roundness

Note 2: Overall layout of product rotation of conductors and or pair(s) may vary to insure best possible roundness and look of product

Jacket: Wall: **0.038”** Nom: **0.260” ± 0.010” x .350” on Steel Cable Side**

Compound: **157-V**

Color: **See Note 4**

Note 3: Print/Markings on Product may vary to better suit Industry approvals. Print Shall be indented

Note 4: This Specification Covers Jacket Colors White-Black

E174416 RU AWM 20811 105°C 600V or AWM 2661 105°C 300V VW-1 cRU AWM I/II A 105°C 600V FT-1

Wire Processed Under Pendant Systems Intertek Control # 4001708



Approvals: **RoHS** **UL 10958/2661/20811** **CSA** **AWM** **Rating: 300V&600V/105°C**

“This Cable Design is the intellectual property of Pendant Systems Mfg. intended for use by Pendant Systems Mfg. and their customers. Treat this as a confidential controlled document”

Proprietary information ***THIS DOCUMENT CAN ONLY BE DUPLICATED WITH THE WRITTEN PERMISSION FROM PENDANT SYSTEMS MFG.***